

# Package ‘GenomicDistributionsData’

November 26, 2024

**Title** Reference data for GenomicDistributions package

**Version** 1.15.0

**Description** This package provides ready to use reference data for GenomicDistributions package. Raw data was obtained from ensemblDb and processed with helper functions. Data files are available for the following genome assemblies: hg19, hg38, mm9 and mm10.

**License** BSD\_2\_clause + file LICENSE

**biocViews** ExperimentHub, ExperimentData, Genome

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.1

**Depends** R (>= 4.1)

**Imports** ExperimentHub (>= 1.14.0), AnnotationHub, AnnotationFilter, data.table, utils, BSgenome, GenomeInfoDb, GenomicFeatures, GenomicRanges, ensemblDb

**Suggests** knitr, BiocStyle, rmarkdown

**VignetteBuilder** knitr

**BugReports** <http://github.com/databio/GenomicDistributionsData>

**git\_url** <https://git.bioconductor.org/packages/GenomicDistributionsData>

**git\_branch** devel

**git\_last\_commit** b1554ea

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.21

**Date/Publication** 2024-11-26

**Author** Michal Stolarczyk [aut],  
Kristyna Kupkova [aut, cre],  
Jose Verdezoto [aut],  
John Lawson [ctb],  
Jason Smith [ctb],  
Nathan C. Sheffield [ctb]

**Maintainer** Kristyna Kupkova <kristynakupkova@gmail.com>

## Contents

.requireAndReturn	2
buildChromSizes	3
buildGeneModels	3
buildOpenSignalMatrix	4
buildTSS	4
cellTypeMetadata	5
chromSizes_hg19	5
chromSizes_hg38	6
chromSizes_mm10	7
chromSizes_mm9	7
geneModels_hg19	8
geneModels_hg38	9
geneModels_mm10	9
geneModels_mm9	10
GenomicDistributionsData	11
loadBSgenome	11
loadEnsDb	12
loadTxDb	13
openSignalMatrix_hg19	13
openSignalMatrix_hg38	14
openSignalMatrix_mm10	15
TSS_hg19	16
TSS_hg38	17
TSS_mm10	18
TSS_mm9	18
<b>Index</b>	<b>20</b>

---

.requireAndReturn	<i>Checks to make sure a package object is installed, and if so, returns it. If the library is not installed, it issues a warning and returns NULL.</i>
-------------------	---

---

## Description

Checks to make sure a package object is installed, and if so, returns it. If the library is not installed, it issues a warning and returns NULL.

## Usage

```
.requireAndReturn(BSgenomeString)
```

## Arguments

BSgenomeString A BSgenome compatible genome string.

**Value**

A BSgenome object if installed.

---

buildChromSizes	<i>Build chromosome sizes object</i>
-----------------	--------------------------------------

---

**Description**

Build chromosome sizes object

**Usage**

```
buildChromSizes(assembly)
```

**Arguments**

assembly      string, reference assembly identifier to chromosome sizes for

**Value**

named int, sizes of chromosome with respective names

**Examples**

```
## Not run:  
buildChromSizes("hg19")  
  
## End(Not run)
```

---

buildGeneModels	<i>Build gene models</i>
-----------------	--------------------------

---

**Description**

Build gene models

**Usage**

```
buildGeneModels(refAssembly)
```

**Arguments**

refAssembly      string, reference assembly identifier to build gene model for

**Value**

a list of four GRanges objects: genesGR, exonsGR, threeUTRGR, fiveUTRGR

**Examples**

```
## Not run:  
hg19models = buildGeneModels("hg19")  
  
## End(Not run)
```

---

buildOpenSignalMatrix *Build open signal matrix*

---

**Description**

Build open signal matrix

**Usage**

```
buildOpenSignalMatrix(assembly)
```

**Arguments**

assembly            string, reference assembly identifier to build gene model for

**Value**

data.frame, rows represent whole selection of open chromatin regions across all cell types defined by ENCODE, columns are individual cell types and values are normalized open chromatin signal values

**Examples**

```
## Not run:  
buildOpenSignalMatrix("hg19")  
  
## End(Not run)
```

---

buildTSS            *Build TSS*

---

**Description**

Build TSS

**Usage**

```
buildTSS(assembly)
```

**Arguments**

assembly            string, reference assembly identifier to TSS for

**Value**

GRanges object that consists of transcription start sites locations

**Examples**

```
## Not run:
tss = buildTSS("hg19")

## End(Not run)
```

---

cellTypeMetadata	<i>Table the maps cell types to tissues and groups</i>
------------------	--

---

**Description**

Table the maps cell types to tissues and groups

**Format**

data.table with 3 columns (cellType, tissue and group) and 74 rows (one per cellType)

**Source**

self-curated dataset

---

chromSizes_hg19	<i>hg19 chromosome sizes</i>
-----------------	------------------------------

---

**Description**

A dataset containing chromosome sizes for Homo sapiens hg19 genome assembly

**Usage**

```
chromSizes_hg19(metadata=FALSE)
```

**Arguments**

metadata            logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

A named vectors of lengths with one item per chromosome

**Value**

A vector of lengths

**Source**

BSgenome.Hsapiens.UCSC.hg19 package

**Examples**

```
hg19c = chromSizes_hg19()
```

---

chromSizes_hg38	<i>hg38 chromosome sizes</i>
-----------------	------------------------------

---

**Description**

A dataset containing chromosome sizes for Homo sapiens hg38 genome assembly

**Usage**

```
chromSizes_hg38(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A named vectors of lengths with one item per chromosome

**Value**

A vector of lengths

**Source**

BSgenome.Hsapiens.UCSC.hg38 package

**Examples**

```
hg38c = chromSizes_hg38()
```

---

chromSizes_mm10	<i>mm10 chromosome sizes</i>
-----------------	------------------------------

---

**Description**

A dataset containing chromosome sizes for Mus musculus mm10 genome assembly

**Usage**

```
chromSizes_mm10(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A named vectors of lengths with one item per chromosome

**Value**

A vector of lengths

**Source**

BSgenome.MMusculus.UCSC.mm10 package

**Examples**

```
mm10c = chromSizes_mm10()
```

---

chromSizes_mm9	<i>mm9 chromosome sizes</i>
----------------	-----------------------------

---

**Description**

A dataset containing chromosome sizes for Mus musculus mm9 genome assembly

**Usage**

```
chromSizes_mm9(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A named vectors of lengths with one item per chromosome

**Value**

A vector of lengths

**Source**

BSgenome.MMusculus.UCSC.mm9 package

**Examples**

```
mm9c = chromSizes_mm9()
```

---

geneModels_hg19	<i>hg19 gene models</i>
-----------------	-------------------------

---

**Description**

A dataset containing gene models for Homo sapiens hg19 genome assembly

**Usage**

```
geneModels_hg19(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A list of two GRanges objects, with genes and exons locations

**Value**

A list with two GRanges objects.

**Source**

EnsDb.Hsapiens.v75 package

**Examples**

```
hg19GeneModels = geneModels_hg19()
```



---

geneModels_hg38	<i>hg38 gene models</i>
-----------------	-------------------------

---

**Description**

A dataset containing gene models for Homo sapiens hg38 genome assembly

**Usage**

```
geneModels_hg38(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A list of two GRanges objects, with genes and exons locations

**Value**

A list with two GRanges objects.

**Source**

EnsDb.Hsapiens.v86 package

**Examples**

```
hg38GeneModels = geneModels_hg38()
```

---

geneModels_mm10	<i>mm10 gene models</i>
-----------------	-------------------------

---

**Description**

A dataset containing gene models for Mus musculus mm10 genome assembly

**Usage**

```
geneModels_mm10(metadata=FALSE)
```

**Arguments**

metadata      logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

A list of two GRanges objects, with genes and exons locations

**Value**

A list with two GRanges objects.

**Source**

EnsDb.Mmusculus.v79 package

**Examples**

```
mm10GeneModels = geneModels_mm10()
```

---

geneModels_mm9	<i>mm9 gene models</i>
----------------	------------------------

---

**Description**

A dataset containing gene models for Mus musculus mm9 genome assembly

**Usage**

```
geneModels_mm9(metadata=FALSE)
```

**Arguments**

metadata      logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

A list of two GRanges objects, with genes and exons locations

**Value**

A list with two GRanges objects.

**Source**

TxDb.Mmusculus.UCSC.mm9.knownGene package

**Examples**

```
mm9GeneModels = geneModels_mm9()
```

---

GenomicDistributionsData  
*GenomicDistributionsData*

---

**Description**

Data (hg19, hg38, mm9, mm10) for the GenomicDistributions package.

**Details**

The vignette details how to access the data from ExperimentHub: `browseVignettes("GenomicDistributionsData")`  
Details on how the data files were created can be found under the R directory in `utils.R` and `build.R`

**Source**

UCSC hg19, hg38, mm9, mm10 genome packages and ensemblDb

**Examples**

```
## Not run:  
library(ExperimentHub)  
hub = ExperimentHub()  
q = query(hub, "GenomicDistributionsData")  
q[[1]]  
q[["EH3472"]]  
  
## End(Not run)
```

---

`loadBSgenome`                      *Loads BSgenome objects from UCSC-style character vectors.*

---

**Description**

This function will let you use a simple character vector (e.g. 'hg19') to load and then return BSgenome objects. This lets you avoid having to use the more complex annotation for a complete BSgenome object (e.g. BSgenome.Hsapiens.UCSC.hg38.masked)

**Usage**

```
loadBSgenome(genomeBuild, masked = TRUE)
```

**Arguments**

genomeBuild     One of 'hg19', 'hg38', 'mm10', 'mm9', or 'grch38'  
masked            Should we used the masked version? Default:TRUE

**Value**

a BSgenome object according to the specified genome assembly

**Examples**

```
## Not run:  
bsg = loadBSgenome('hg19')  
  
## End(Not run)
```

---

loadEnsDb	<i>Load selected EnsDb library</i>
-----------	------------------------------------

---

**Description**

Load selected EnsDb library

**Usage**

```
loadEnsDb(genomeBuild)
```

**Arguments**

genomeBuild     string, genome identifier

**Value**

loaded library

**Examples**

```
## Not run:  
loadEnsDb("hg19")  
  
## End(Not run)
```

---

loadTxDb	<i>Load selected TxDb library</i>
----------	-----------------------------------

---

**Description**

Load selected TxDb library

**Usage**

```
loadTxDb(genomeBuild)
```

**Arguments**

genomeBuild     string, genome identifier

**Value**

loaded library

**Examples**

```
## Not run:  
loadTxDb("hg19")  
  
## End(Not run)
```

---

openSignalMatrix\_hg19 *A dataset containing open chromatin regions across all cell types defined by ENCODE for Homo Sapiens hg19*

---

**Description**

Preparation steps:

1. made a universe of regions by merging regions across cell types defined as opened in ENCODE
2. took bigwig files from ENCODE for individual cell types, merged replicates, filtered out blacklisted sites
3. evaluated the signal above regions defined by previous step
4. performed quantile normalization

**Usage**

```
openSignalMatrix_hg19(metadata=FALSE)
```

**Arguments**

metadata            logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

data.frame, rows represent whole selection of open chromatin regions across all cell types defined by ENCODE, columns are individual cell types and values are normalized open chromatin signal values.

**Value**

A data.frame with hg19 open chromatin regions.

**Source**

[http://big.databio.org/open\\_chromatin\\_matrix/openSignalMatrix\\_hg19\\_percentile99\\_01\\_quantNormalized\\_round4d.txt.gz](http://big.databio.org/open_chromatin_matrix/openSignalMatrix_hg19_percentile99_01_quantNormalized_round4d.txt.gz)

**Examples**

```
## Not run:  
hg19OpenSignal = openSignalMatrix_hg19()  
  
## End(Not run)
```

---

openSignalMatrix\_hg38 *A dataset containing open chromatin regions across all cell types defined by ENCODE for Homo sapiens hg38*

---

**Description**

Preparation steps:

1. made a universe of regions by merging regions across cell types defined as opened in ENCODE
2. took bigwig files from ENCODE for individual cell types, merged replicates, filtered out blacklisted sites
3. evaluated the signal above regions defined by previous step
4. performed quantile normalization

**Usage**

```
openSignalMatrix_hg38(metadata=FALSE)
```

**Arguments**

metadata            logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

data.frame, rows represent whole selection of open chromatin regions across all cell types defined by ENCODE, columns are individual cell types and values are normalized open chromatin signal values.

**Value**

A data.frame with hg38 open chromatin regions.

**Source**

[http://big.databio.org/open\\_chromatin\\_matrix/openSignalMatrix\\_hg38\\_percentile99\\_01\\_quantNormalized\\_round4d.txt.gz](http://big.databio.org/open_chromatin_matrix/openSignalMatrix_hg38_percentile99_01_quantNormalized_round4d.txt.gz)

**Examples**

```
## Not run:  
hg38OpenSignal = openSignalMatrix_hg38()  
  
## End(Not run)
```

---

openSignalMatrix\_mm10 *A dataset containing open chromatin regions across all cell types defined by ENCODE for Mus musculus mm10*

---

**Description**

Preparation steps:

1. made a universe of regions by merging regions across cell types defined as opened in ENCODE
2. took bigwig files from ENCODE for individual cell types, merged replicates, filtered out blacklisted sites
3. evaluated the signal above regions defined by previous step
4. performed quantile normalization

**Usage**

```
openSignalMatrix_mm10(metadata=FALSE)
```

**Arguments**

metadata            logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

data.frame, rows represent whole selection of open chromatin regions across all cell types defined by ENCODE, columns are individual cell types and values are normalized open chromatin signal values.

**Value**

A data.frame with mm10 open chromatin regions.

**Source**

[http://big.databio.org/open\\_chromatin\\_matrix/openSignalMatrix\\_mm10\\_percentile99\\_01\\_quantNormalized\\_round4d.txt.gz](http://big.databio.org/open_chromatin_matrix/openSignalMatrix_mm10_percentile99_01_quantNormalized_round4d.txt.gz)

**Examples**

```
## Not run:
mm10OpenSignal = openSignalMatrix_mm10()

## End(Not run)
```

---

TSS\_hg19

*hg19 TSS locations*

---

**Description**

A dataset containing Transcription Start Sites for Homo sapiens hg19 genome assembly

**Usage**

```
TSS_hg19(metadata=FALSE)
```

**Arguments**

metadata            logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

A GRanges object with Transcription Start Site locations



**Value**

A GRanges object with hg19 TSS locations.

**Source**

EnsDb.Hsapiens.v75 package

**Examples**

```
hg19TSS = TSS_hg19()
```

---

TSS\_hg38

*hg38 TSS locations*

---

**Description**

A dataset containing Transcription Start Sites for the Homo sapiens hg38 genome assembly

**Usage**

```
TSS_hg38(metadata=FALSE)
```

**Arguments**

metadata      logical value indicating whether only metadata should be returned or if the resource should be loaded

**Format**

A GRanges object with Transcription Start Site locations

**Value**

A GRanges object with hg38 TSS locations.

**Source**

EnsDb.Hsapiens.v86 package

**Examples**

```
hg38TSS = TSS_hg38()
```

---

TSS_mm10	<i>mm10 TSS locations</i>
----------	---------------------------

---

**Description**

A dataset containing Transcription Start Sites for the Mus musculus mm10 genome assembly

**Usage**

```
TSS_mm10(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A named vectors of lengths with one item per chromosome

**Value**

A GRanges object with mm10 TSS locations.

**Source**

Ensembl.Mmusculus.v79 package

**Examples**

```
mm10TSS = TSS_mm10()
```

---

TSS_mm9	<i>mm9 TSS locations</i>
---------	--------------------------

---

**Description**

A dataset containing Transcription Start Sites for the Mus musculus mm9 genome assembly

**Usage**

```
TSS_mm9(metadata=FALSE)
```

**Arguments**

metadata	logical value indicating whether only metadata should be returned or if the resource should be loaded
----------	---

**Format**

A named vectors of lengths with one item per chromosome

**Value**

A GRanges object with mm9 TSS locations.

**Source**

TxDb.Mmusculus.UCSC.mm9.knownGene package

**Examples**

```
mm9TSS = TSS_mm9()
```

# Index

## \* datasets

- cellTypeMetadata, 5
- chromSizes\_hg19, 5
- chromSizes\_hg38, 6
- chromSizes\_mm10, 7
- chromSizes\_mm9, 7
- geneModels\_hg19, 8
- geneModels\_hg38, 9
- geneModels\_mm10, 9
- geneModels\_mm9, 10
- openSignalMatrix\_hg19, 13
- openSignalMatrix\_hg38, 14
- openSignalMatrix\_mm10, 15
- TSS\_hg19, 16
- TSS\_hg38, 17
- TSS\_mm10, 18
- TSS\_mm9, 18

.requireAndReturn, 2

buildChromSizes, 3

buildGeneModels, 3

buildOpenSignalMatrix, 4

buildTSS, 4

cellTypeMetadata, 5

chromSizes\_hg19, 5

chromSizes\_hg38, 6

chromSizes\_mm10, 7

chromSizes\_mm9, 7

geneModels\_hg19, 8

geneModels\_hg38, 9

geneModels\_mm10, 9

geneModels\_mm9, 10

GenomicDistributionsData, 11

loadBSgenome, 11

loadEnsDb, 12

loadTxDb, 13

openSignalMatrix\_hg19, 13

openSignalMatrix\_hg38, 14

openSignalMatrix\_mm10, 15

TSS\_hg19, 16

TSS\_hg38, 17

TSS\_mm10, 18

TSS\_mm9, 18